

UT265B/UT267B are economical 2/3 phase clamp meters. These meters are able to simultaneously measure 2/3 phase systems and display phase diagram on the LCD screen. These meters can be used to monitor power distribution box, suitable for electricians, electrical maintenance, repair, and training personnel.

### SPECIFICATIONS

	Range	UT265B	UT267B
AC current (A)	0mA~20A	±(1.5%+3)	±(1.5%+3)
AC voltage (V)	0V~600V	±(1.5%+3)	±(1.5%+3)
Frequency (Hz)	45Hz~65Hz	±(2%+3)	±(2%+3)
Active power (W)	0W~12kW	±(3%+3)	±(3%+3)
Apparent power (VA)	0VA~12kVA	±(3%+3)	±(3%+3)
Reactive power (VAR)	0VAR~12kVAR	±(3%+3)	±(3%+3)
Power factor	-1~+1	±0.03	±0.03
Phase angle (°)	0°~360°	±1°	±1°
Current vector sum	0mA~60A		√
Phase sequence test	Forward rotation, U1-U2-U3 or I1-I2-I3; reverse rotation, U1-U3-U2 or I1-I3-I2		√

#### Features

Display mode	LCD: 240 dots×160 dots	√	√
Clamp size	Acuminate current clamp: 7.5mm×13mm (optional) Round jaw current clamp: 35mm×40mm (optional)		
Auto range		√	√
RS-232		√	√
Data storage		1500	99
LCD backlight		√	√
Data hold		√	√
Input impedance for DCV	≥2MΩ	√	√
Auto power off	About 15 minutes	√	√
Low battery indication		√	√
Sampling rate	About 0.5 times/s	√	√



● UT267B

### GENERAL CHARACTERISTICS

Power	1.5V battery (LR6) x 6
Product color	Red and grey
Product net weight	550g
Product size	196mm x 92mm x 54mm
Standard accessories	Batteries, current clamps ( <b>UT265B</b> : 2pcs; <b>UT267B</b> : 3pcs), test leads ( <b>UT265B</b> : 2 yellow, 2 black; <b>UT267B</b> : 1 yellow, 1 green, 1 red, 1 black)
Standard individual packing	Gift box, tool box, English manual
Standard quantity per carton	1pcs
Standard carton measurement	337mm x 136mm x 333mm
Standard carton gross weight	3.3kg