



UT363S is a stable, safe and reliable split-type anemometer, featuring quick detection, low consumption and high accuracy. It can be widely used in mining, electric, iron and steel, petrochemical, energy-saving, navigation, fan manufacturing, exhaust ventilation, sporting and more sectors.



SPECIFICATIONS

	Range	Resolution	Accuracy
Wind speed	0.4~30m/s	0~99: 0.01	±(5%+0.5m/s)
	1.4~108km/h		±(5%+1.5km/h)
	78~5905ft/min	100~999: 0.1	±(5%+100ft/min)
	0.7~58knots	≥1000: 1	±(5%+1knots)
	0.8~67mph		±(5%+1mph)
Temperature	-10~50°C	0.1°C	±2.0°C
	14~122°F	0.2°F	±4.0°F
Wind scale	0~12	1	±1

Features

Sampling rate	0.5s
Units	m/s, km/h, ft/min, knots, mph, °C/°F
Overload indication	√
Auto range	√
Auto power off	√
Low battery indication	√
Data hold	√
MAX/MIN/AVG	√
Backlight	√
Working temperature	0°C~40°C
1m drop test	√

GENERAL CHARACTERISTICS

Power	1.5V battery (R03) x 3
Display	35mm x 32mm
Product color	Red and grey
Product net weight	365g
Product size	120mm x 53mm x 43mm
Standard accessories	Batteries
Standard individual packing	Gift box, blister, English manual
Standard quantity per carton	20pcs
Standard carton measurement	550mm x 295mm x 350mm
Standard carton gross weight	7.2kg