



- Split probe
- Sampling time: 0.5s
- Auto range
- Lux/Fc selectable
- Max/Min
- Overload indication (LO/HI)
- Data hold
- Backlight
- Auto power off
- Low battery indication

Applications:

Public settings, light manufacturing, photo studios, interior renovation, construction, greenhouses.

SPECIFICATIONS

	Range	Resolution	Accuracy
Illuminance	0~199,900Lux	1Lux (0~9999Lux)	±(4%+8)
		10Lux (≥10,000Lux)	±(5%+10)
		100Lux (≥100,000Lux)	±(5%+10)
		0.1Fc (0~999.9Fc)	FC=Lux/10.76
		1Fc (≥1000Fc)	
		10Fc (≥10,000Fc)	

Features

MAX/MIN	√
Data hold	√
Overload indication	√
Backlight	√
Auto power off	√

GENERAL CHARACTERISTICS

Power	1.5V battery (R03) x 3
Display	35mm x 32mm
Product color	Red and grey
Product net weight	300g
Product size	110mm x 53mm x 26mm
Standard accessories	Batteries
Standard individual packing	Blister, gift box, English manual
Standard quantity per carton	20pcs
Standard carton measurement	560mm x 300mm x 335mm
Standard carton gross weight	6.9kg