

A12T/A13T Temperature Humidity Meters



A137

15:58



A12T/13T measures real-time temperature and humidity and display readings on a large screen. These can be used for both indoor and outdoor measurements. A12T has an additional external sensor probe for measuring temperatures of two locations. Both of these meters have alarm clock and 12/24 time mode. A12T displays comfort rating based on the combination of temperature and humidity. Hanging hole and stand are available for wall or table mount.

Applications: Labs, offices, hotels, schools, factories, meeting rooms, airports, pharmacies, warehouses, restaurants, greenhouses, nurseries, gardens, homes, shopping malls, museums, animal husbandry, and more.



SPECIFICATIONS

	Range	A12T	A13T
Temperature (°C)	-10°C~50°C	±1°C (0~40°C)	±1°C (0~40°C)
Humidity	20%~95%RH	±5%RH (40%~80%RH)	±5%RH (40%~80%RH)
External temperature probe	-10°C~50°C	±1°C (0~40°C)	
Features			·
°C/°F selection		√	√
MAX/MIN		√	
Comfort rating	Wet/dry/comfort	√	
Sampling time	10s	√	
Alarm clock/time display		√	√
Date/calendar			√
12/24 hour modes		√	√
External temperature probe		√	

I GENERAL CHARACTERISTICS

Power	1.5V battery (R03) x 1
Display	92.5mm x 60mm
Product color	White
Product net weight	110g
Product size	130mm x 22mm x 78mm
Standard accessories	Batteries, External Temperature Probe (A12T)
Standard individual packing	Gift box, bubble bag, English manual
Standard quantity per carton	80pcs
Standard carton measurement	400mm x 330mm x 290mm
Standard carton gross weight	A12T: 13.2kg; A13T: 12.2kg