

DT-9011/9011B/9020/9021/9030/9120/9121/9130

Electrical Testers



EMC & LVD

EN: 61326

TN: 61010-1

EN: 61243

EN: 61010-3 (9030/9130)



- Double molded plastic housing
- CAT III 1000V

- Bright Flashlight
- VAT self-test button

Features

| | 9011/9011B | 9020/9120 | 9021/9121 | 9030/9130 |
|--|------------|-----------|-----------|-----------|
| Clear LED indication | * | * | * | |
| 1999 counts LCD display with analog bargraph | | | | * |
| AC/DC Voltage detection | * | * | * | * |
| Polarity detection | * | * | * | * |
| Single-pole phase test | | | * | |
| Continuity test | | | * | * |
| Rotary field indication | | | * | * |
| Low impedance test | * | * | * | * |
| Flashlight | | * | * | * |
| Voltage function operates without battery | * | * | | |
| IP64 | * | * | * | * |
| Overvoltage class CATIII 1000V/CATIV 600V | | * | * | * |
| VAT self-test button | | -/* | -/* | -/* |

Specifications

| | 9011/9011B | 9020/9120 | 9021/9121 | 9030/9130 |
|-----------------------|-------------------------|--------------------------|--------------------------|--------------------------|
| Voltage range (AC/DC) | 6,12,24,50,120,230,400V | 12,24,36,50,120,230,400V | 12,24,36,50,120,230,400V | 12,24,36,50,120,230,400V |
| Tolerance | -30% to 0% of reading | -30% to 0% of reading | -30% to 0% of reading | ±1.5%±3D |
| ACV Frequency range | 0~60Hz | 0~60Hz | 0~60Hz | 50/60Hz |
| Internal impedance | - | <200kΩ/- | <200kΩ/- | ≤1MΩ/- |

Size(HxWxD): 240mm x 78mm x 40mm

Weight: 237g

Accessories:

Two "AAA" batteries (9021/9030/9121), gift box with carrying case

